

# Camaro PUR

## PRODUCT SPECIFICATION

### Key Features

- > Wood, parquet & stone designs
- > Multiple plank & tile sizes
- > Inlay accessories available
- > Low VOC emissions
- > Light commercial & residential interiors



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.30mm
Total Weight	ISO 23997 (EN 430)	3600g/m <sup>2</sup>
Finish		PUR

Plank & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	Size Mix	1	36	3.62m <sup>2</sup>
	76.2mm x 228.6mm	2	192	3.34m <sup>2</sup>
	76.2mm x 457.2mm	3	96	3.34m <sup>2</sup>
	101.6mm x 914.4mm	1	36	3.34m <sup>2</sup>
	152.4mm x 914.4mm	1	24	3.34m <sup>2</sup>
	152.4mm x 1219.2mm	1	18	3.34m <sup>2</sup>
	184.2mm x 1219.2mm	13	15	3.37m <sup>2</sup>
Tile	304.8mm x 304.8mm	1	36	3.34m <sup>2</sup>
	304.8mm x 609.6mm	7	18	3.34m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 10582 (EN 649)	Conforms
Use Area	ISO 10874 (EN 685)	23, 31
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥ 0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 <450 Pass Class 1 FSV < 300; SDV < 500

<b>Static Electrical Propensity</b>	EN 1815	≤2.0kV Classified as 'antistatic'
<b>Residual Indentation</b>	ISO 24343-1 ASTM F970 ASTM F1914	<0.05mm* ≤0.005" @ 750psi ≤0.005"
<b>Castor Chair (continuous use)</b>	ISO 4918 (EN 425)	Suitable
<b>Dimensional Stability</b>	ISO 23999 (EN 434) ASTM F2199	≤0.10% Pass
<b>Underfloor Heating</b>		Suitable, max 27°C
<b>Light Fastness</b>	ISO 105-B02 (Method 3)	≥6
<b>Resistance to Light</b>	ASTM F1515	ΔE ≤ 8.0 - Meets
<b>Resistance to Heat</b>	ASTM F1514	ΔE ≤ 8.0 - Meets

\*Average test value from current production.

## Sustainability

	Standard	Result
<b>BRE Green Guide</b>		A+ ENP 429
<b>GreenTag</b>	LCA Rate Gold Plus	GreenRate level A
<b>Generic EN 15804 EPD</b>		Available
<b>Recyclable</b>		100%
<b>Recycled Content</b>		Up to 40%
<b>REACH</b>		Compliant
<b>Indoor Air Comfort Gold</b>		Eurofins certified product
<b>FloorScore</b>		Certified
<b>Finnish M1 Classification</b>		Certified
<b>AgBB/ABG</b>		Pass
<b>Responsible Sourcing</b>	BES 6001 SA 8000	Very good Approved Factory

## Acoustic Performance

	Standard	Result
<b>Impact Sound Reduction</b>	ISO 10140-3	2dB
<b>Sound Transmission Coefficient</b>	ASTM E90/492	STC 55
<b>Impact Insulation Class</b>	ASTM E90/492	IIC 39

## Maintenance Performance

	Standard	Result
<b>Resistance to Chemicals</b>	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



## Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

# Camaro PUR



## RANGE SHADES

**76.2mm x 228.6mm**  
3" x 9"



Cambridge Parquet **2251**  
LRV 27



Georgian Parquet **2252**  
LRV 16

**76.2mm x 457.2mm**  
3" x 18"



Naked Blond Oak  
Large Parquet **LPQ2257**  
LRV 36



Westchester Oak  
Large Parquet **LPQ2253**  
LRV 39



Waterside Oak  
Large Parquet **LPQ2256**  
LRV 39

**101.6mm x 914.4mm**  
4" x 36"



Nut Tree **2202** LRV 29

**152.4mm x 914.4mm**  
6" x 36"



Smoke Brushed Elm **2233** LRV 25

## Size Mix

Planks are supplied in 3 widths,  
36 planks per box, (12 planks of each size).

**76.2 / 101.6 / 152.4mm x 914.4mm**  
3/4/6" x 36"

Salvaged Timber **2247** LRV 23

**152.4mm x 1219.2mm**  
6" x 48"



Natural Oak **2232** LRV 22

**184.2mm x 1219.2mm**  
7.25" x 48"



Naked Blond Oak **PLK2257** LRV 36



Westchester Oak **PLK2253** LRV 39



Waterside Oak **PLK2256** LRV 39



Bianco Oak **2241** LRV 46

**184.2mm x 1219.2mm (continued)**

7.25" x 48"



Rosedale Oak **2254**

LRV 42



Boathouse Oak **2242**



LRV 27



Fenland Oak **2258**

LRV 30



Quayside Oak **2246**

LRV 30



Cashmere Oak **2244**

LRV 32



Sienna Oak **2248**

LRV 29



Astoria Oak **2259**



LRV 20



Wild Amber Oak **2249**



LRV 19




Bayswater Oak **2261**

LRV 25


**Camaro PUR**

**304.8mm x 304.8mm**  
12" x 12"




Atlantic Slate **2339**  
LRV 8


**304.8mm x 609.6mm**  
12" x 24"




Arctic Slate **2341** LRV 53




White Metalstone **2332** LRV 57




Soho Cement **2347** LRV 50



Burnished Concrete **2342** LRV 37



Tribeca Cement **2348** LRV 39




Goldstone Micro Terrazzo **2349** LRV 29



Ocean Slate **2319** LRV 23

LRV - Light Reflectance Value

 Micro Bevelled Edges

 Colour/Pattern Variation

**Polyflor Ltd. Head Office**

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.